

**NEUTRAL SILICONE WEATHER SEALANT  
CLEAR**

Version 7.0      Revision Date: 21.11.2024      SDS Number: 10591859-00011      Date of last issue: 19.06.2024  
Date of first issue: 17.03.2011

---

**SECTION 1: IDENTIFICATION**

Product name : NEUTRAL SILICONE WEATHER SEALANT CLEAR  
Product code : 0892 538 81

**Manufacturer or supplier's details**

Company : Wurth Australia Pty. Ltd.  
Address : Building 5, 43 - 63 Princes Highway  
Dandenong South, VIC 3175  
Telephone : +61 3 8788 1111  
Emergency telephone number : 1300 657 765. Advisory office in case of poisoning - National  
Poisons Centre: 131 126  
E-mail address : product@wurth.com.au

**Recommended use of the chemical and restrictions on use**

Recommended use : Sealant  
Restrictions on use : Not applicable

---

**SECTION 2. HAZARDS IDENTIFICATION****GHS Classification**

Serious eye damage/eye irritation : Category 2A  
Skin sensitisation : Category 1  
Carcinogenicity : Category 1B  
Specific target organ toxicity - single exposure (Inhalation) : Category 2 (Upper respiratory tract)

**GHS label elements**

Hazard pictograms :   
Signal word : Danger

## NEUTRAL SILICONE WEATHER SEALANT CLEAR

Version 7.0      Revision Date: 21.11.2024      SDS Number: 10591859-00011      Date of last issue: 19.06.2024  
Date of first issue: 17.03.2011

Hazard statements	:	H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H350 May cause cancer. H371 May cause damage to organs (Upper respiratory tract) if inhaled.
Precautionary statements	:	<p><b>Prevention:</b></p> <p>P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P260 Do not breathe vapours. P264 Wash skin thoroughly after handling. P270 Do not eat, drink or smoke when using this product. P271 Use only outdoors or in a well-ventilated area. P272 Contaminated work clothing should not be allowed out of the workplace. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</p> <p><b>Response:</b></p> <p>P302 + P352 IF ON SKIN: Wash with plenty of water. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308 + P311 IF exposed or concerned: Call a POISON CENTER/ doctor. P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention. P337 + P313 If eye irritation persists: Get medical advice/ attention.</p> <p><b>Storage:</b></p> <p>P405 Store locked up.</p> <p><b>Disposal:</b></p> <p>P501 Dispose of contents/ container to an approved waste disposal plant.</p>

### Other hazards which do not result in classification

None known.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

#### Components

Chemical name	CAS-No.	Concentration (% w/w)
Distillates (petroleum), hydrotreated middle	64742-46-7	>= 10 -< 30

## NEUTRAL SILICONE WEATHER SEALANT CLEAR

Version 7.0      Revision Date: 21.11.2024      SDS Number: 10591859-00011      Date of last issue: 19.06.2024  
Date of first issue: 17.03.2011

Butan-2-one O,O',O''-(methylsilyldiyl)trioxime	22984-54-9	>= 1 -< 10
Ethyl methyl ketoxime	96-29-7	>= 1 -< 3
Butan-2-one O,O',O''-(vinylsilyldiyl)trioxime	2224-33-1	>= 0.1 -< 1
3-(2-Aminoethylamino) propyltrimethoxysilane	1760-24-3	>= 0.1 -< 1

### SECTION 4. FIRST AID MEASURES

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.  
Get medical attention.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water.  
Remove contaminated clothing and shoes.  
Get medical attention.  
Wash clothing before reuse.  
Thoroughly clean shoes before reuse.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.  
If easy to do, remove contact lens, if worn.  
Get medical attention.
- If swallowed : If swallowed, DO NOT induce vomiting.  
Get medical attention.  
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : May cause an allergic skin reaction.  
Causes serious eye irritation.  
May cause cancer.  
May cause damage to organs if inhaled.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- Notes to physician : Treat symptomatically and supportively.

### SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Water spray  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing : None known.

**NEUTRAL SILICONE WEATHER SEALANT  
CLEAR**

Version	Revision Date:	SDS Number:	Date of last issue: 19.06.2024
7.0	21.11.2024	10591859-00011	Date of first issue: 17.03.2011

---

media

Specific hazards during fire-fighting : Exposure to combustion products may be a hazard to health.

Hazardous combustion products : Carbon oxides  
Silicon oxides  
Nitrogen oxides (NO<sub>x</sub>)

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.

---

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment.  
Prevent further leakage or spillage if safe to do so.  
Prevent spreading over a wide area (e.g. by containment or oil barriers).  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material.  
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container.  
Clean up remaining materials from spill with suitable absorbent.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

## NEUTRAL SILICONE WEATHER SEALANT CLEAR

Version	Revision Date:	SDS Number:	Date of last issue: 19.06.2024
7.0	21.11.2024	10591859-00011	Date of first issue: 17.03.2011

### SECTION 7. HANDLING AND STORAGE

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.
- Advice on safe handling : Do not get on skin or clothing.  
Do not breathe vapours.  
Do not swallow.  
Do not get in eyes.  
Wash skin thoroughly after handling.  
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment  
Keep container tightly closed.  
Keep away from water.  
Protect from moisture.  
Do not eat, drink or smoke when using this product.  
Take care to prevent spills, waste and minimize release to the environment.
- Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.  
When using do not eat, drink or smoke.  
Contaminated work clothing should not be allowed out of the workplace.  
Wash contaminated clothing before re-use.
- Conditions for safe storage : Keep in properly labelled containers.  
Store locked up.  
Keep tightly closed.  
Store in accordance with the particular national regulations.
- Materials to avoid : Do not store with the following product types:  
Strong oxidizing agents

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (petroleum), hydrotreated middle	64742-46-7	TWA (Mist)	5 mg/m <sup>3</sup>	AU OEL

**NEUTRAL SILICONE WEATHER SEALANT  
CLEAR**

Version	Revision Date:	SDS Number:	Date of last issue: 19.06.2024
7.0	21.11.2024	10591859-00011	Date of first issue: 17.03.2011

---

**Engineering measures** : Processing may form hazardous compounds (see section 10).  
Minimize workplace exposure concentrations.  
If sufficient ventilation is unavailable, use with local exhaust ventilation.

**Personal protective equipment**

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

Filter type : Combined particulates and organic vapour type

## Hand protection

Material : Nitrile rubber  
Break through time : 10 - 60 min  
Glove thickness : > 0.1 mm

Material : butyl-rubber  
Break through time : > 480 min  
Glove thickness : > 0.3 mm

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:  
Safety goggles

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.  
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

---

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : paste

Colour : colourless

Odour : strong

**NEUTRAL SILICONE WEATHER SEALANT  
CLEAR**

Version	Revision Date:	SDS Number:	Date of last issue: 19.06.2024
7.0	21.11.2024	10591859-00011	Date of first issue: 17.03.2011

---

Odour Threshold : No data available

pH : 7  
Concentration: 100 %

Melting point/freezing point : No data available

Initial boiling point and boiling range : No data available

Flash point : > 250 °C

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Flammability (liquids) : No data available

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapour pressure : No data available

Relative vapour density : No data available

Relative density : 1.00 (23 °C)

Density : 1.00 g/cm<sup>3</sup> (23 °C)

Solubility(ies)  
Water solubility : hydrolyses, Decomposes in contact with water.

Partition coefficient: n-octanol/water : Not applicable

Auto-ignition temperature : ca. 430 °C  
Method: DIN 51794

Decomposition temperature : > 150 °C

Viscosity  
Viscosity, kinematic : > 20.5 mm<sup>2</sup>/s ( 40 °C)

**NEUTRAL SILICONE WEATHER SEALANT  
CLEAR**

Version	Revision Date:	SDS Number:	Date of last issue: 19.06.2024
7.0	21.11.2024	10591859-00011	Date of first issue: 17.03.2011

---

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle characteristics  
Particle size : Not applicable

---

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Use at elevated temperatures may form highly hazardous compounds.  
Can react with strong oxidizing agents.  
Methyl Ethyl Ketoxime (MEKO) is formed upon contact with water or humid air.  
Hazardous decomposition products will be formed upon contact with water or humid air.

Conditions to avoid : Exposure to moisture

Incompatible materials : Oxidizing agents  
Water

**Hazardous decomposition products**

Contact with water or humid air : Ethyl methyl ketoxime

---

**SECTION 11. TOXICOLOGICAL INFORMATION**

Exposure routes : Inhalation  
Skin contact  
Ingestion  
Eye contact

**Acute toxicity**

Not classified based on available information.

**Product:**

Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg  
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2,000 mg/kg  
Method: Calculation method



**NEUTRAL SILICONE WEATHER SEALANT  
CLEAR**

Version 7.0      Revision Date: 21.11.2024      SDS Number: 10591859-00011      Date of last issue: 19.06.2024  
Date of first issue: 17.03.2011

---

**Components:****Distillates (petroleum), hydrotreated middle:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5,000 mg/m<sup>3</sup>  
Exposure time: 4 h  
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg  
Assessment: The substance or mixture has no acute dermal toxicity

**Butan-2-one O,O',O''-(methylsilylidyne)trioxime:**

Acute oral toxicity : LD50 (Rat): 2,453 mg/kg  
Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg  
Method: OECD Test Guideline 402

**Ethyl methyl ketoxime:**

Acute oral toxicity : Acute toxicity estimate: 100 mg/kg  
Method: Expert judgement

Acute inhalation toxicity : LC50 (Rat): > 4.83 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour

Acute dermal toxicity : Acute toxicity estimate: 1,100 mg/kg  
Method: Expert judgement

**Butan-2-one O,O',O''-(vinylsilylidyne)trioxime:**

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg  
Method: OECD Test Guideline 425

Acute dermal toxicity : LD50 (Rat): > 2,009 mg/kg  
Method: OECD Test Guideline 402

**3-(2-Aminoethylamino) propyltrimethoxysilane:**

Acute oral toxicity : LD50 (Rat, female): 1,897 mg/kg  
Method: OPPTS 870.1100

Acute toxicity estimate (Humans): > 300 - 2,000 mg/kg  
Method: Expert judgement  
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): 1.49 - 2.44 mg/l  
Exposure time: 4 h

**NEUTRAL SILICONE WEATHER SEALANT  
CLEAR**

Version 7.0      Revision Date: 21.11.2024      SDS Number: 10591859-00011      Date of last issue: 19.06.2024  
Date of first issue: 17.03.2011

---

Test atmosphere: dust/mist  
Method: OPPTS 870.1300

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg  
Method: OPPTS 870.1200

**Skin corrosion/irritation**

Not classified based on available information.

**Components:****Distillates (petroleum), hydrotreated middle:**

Assessment : Repeated exposure may cause skin dryness or cracking.

**Butan-2-one O,O',O''-(methylsilylidyne)trioxime:**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation

**Ethyl methyl ketoxime:**

Species : Rabbit  
Result : Skin irritation

**Butan-2-one O,O',O''-(vinylsilylidyne)trioxime:**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation

**3-(2-Aminoethylamino) propyltrimethoxysilane:**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : Mild skin irritation

**Serious eye damage/eye irritation**

Causes serious eye irritation.

**Components:****Distillates (petroleum), hydrotreated middle:**

Result : No eye irritation

**Butan-2-one O,O',O''-(methylsilylidyne)trioxime:**

Species : Rabbit  
Result : Irritation to eyes, reversing within 21 days  
Method : OECD Test Guideline 405

**NEUTRAL SILICONE WEATHER SEALANT  
CLEAR**

Version 7.0      Revision Date: 21.11.2024      SDS Number: 10591859-00011      Date of last issue: 19.06.2024  
Date of first issue: 17.03.2011

---

**Ethyl methyl ketoxime:**

Species : Rabbit  
Result : Irreversible effects on the eye

**Butan-2-one O,O',O''-(vinylsilyldiyl)trioxime:**

Species : Rabbit  
Result : Irreversible effects on the eye  
Method : OECD Test Guideline 405

**3-(2-Aminoethylamino) propyltrimethoxysilane:**

Species : Rabbit  
Result : Irreversible effects on the eye  
Method : OECD Test Guideline 405

**Respiratory or skin sensitisation****Skin sensitisation**

May cause an allergic skin reaction.

**Respiratory sensitisation**

Not classified based on available information.

**Components:****Distillates (petroleum), hydrotreated middle:**

Test Type : Human repeat insult patch test (HRIPT)  
Exposure routes : Skin contact  
Result : negative

**Butan-2-one O,O',O''-(methylsilyldiyl)trioxime:**

Test Type : Maximisation Test  
Exposure routes : Skin contact  
Species : Guinea pig  
Result : positive

Assessment : Probability or evidence of skin sensitisation in humans

**Ethyl methyl ketoxime:**

Test Type : Buehler Test  
Exposure routes : Skin contact  
Species : Guinea pig  
Result : positive

Assessment : Probability or evidence of skin sensitisation in humans

**Butan-2-one O,O',O''-(vinylsilyldiyl)trioxime:**

Test Type : Maximisation Test

**NEUTRAL SILICONE WEATHER SEALANT  
CLEAR**

Version 7.0      Revision Date: 21.11.2024      SDS Number: 10591859-00011      Date of last issue: 19.06.2024  
Date of first issue: 17.03.2011

---

Exposure routes : Skin contact  
Species : Guinea pig  
Result : positive  
Remarks : Based on data from similar materials

Assessment : Probability or evidence of skin sensitisation in humans

**3-(2-Aminoethylamino) propyltrimethoxysilane:**

Test Type : Maximisation Test  
Exposure routes : Skin contact  
Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : positive

Assessment : Probability or evidence of high skin sensitisation rate in humans

**Chronic toxicity****Germ cell mutagenicity**

Not classified based on available information.

**Components:****Distillates (petroleum), hydrotreated middle:**

Genotoxicity in vitro : Test Type: In vitro sister chromatid exchange assay in mammalian cells  
Result: negative

**Butan-2-one O,O',O''-(methylsilyldiyl)trioxime:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

**Ethyl methyl ketoxime:**

Genotoxicity in vitro : Test Type: DNA damage and repair, unscheduled DNA synthesis in mammalian cells (in vitro)  
Method: OECD Test Guideline 482  
Result: negative

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis)  
Species: Rat  
Application Route: Ingestion  
Result: negative

**Butan-2-one O,O',O''-(vinylsilyldiyl)trioxime:**

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro  
Method: OECD Test Guideline 473

**NEUTRAL SILICONE WEATHER SEALANT  
CLEAR**

Version 7.0      Revision Date: 21.11.2024      SDS Number: 10591859-00011      Date of last issue: 19.06.2024  
Date of first issue: 17.03.2011

---

Result: positive

Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Mouse  
Application Route: Intraperitoneal injection  
Method: OECD Test Guideline 474  
Result: negative

**3-(2-Aminoethylamino) propyltrimethoxysilane:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative

Test Type: In vitro mammalian cell gene mutation test  
Result: negative

Test Type: In vitro sister chromatid exchange assay in mammalian cells  
Method: OPPTS 870.5900  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Mouse  
Application Route: Intraperitoneal injection  
Result: negative

**Carcinogenicity**

May cause cancer.

**Components:****Butan-2-one O,O',O''-(methylsilyldiyl)trioxime:**

Species : Rat  
Application Route : inhalation (vapour)  
Exposure time : 26 Months  
Result : positive  
Remarks : Based on data from similar materials

Carcinogenicity - Assessment : Sufficient evidence of carcinogenicity in animal experiments

**Ethyl methyl ketoxime:**

Species : Rat

**NEUTRAL SILICONE WEATHER SEALANT  
CLEAR**

Version 7.0      Revision Date: 21.11.2024      SDS Number: 10591859-00011      Date of last issue: 19.06.2024  
Date of first issue: 17.03.2011

---

Application Route : inhalation (vapour)  
Exposure time : 26 Months  
Result : positive

Carcinogenicity - Assessment : Sufficient evidence of carcinogenicity in animal experiments

**Butan-2-one O,O',O''-(vinylsilyldiyl)trioxime:**

Species : Rat  
Application Route : inhalation (vapour)  
Exposure time : 26 Months  
Result : positive  
Remarks : Based on data from similar materials

Carcinogenicity - Assessment : Sufficient evidence of carcinogenicity in animal experiments

**Reproductive toxicity**

Not classified based on available information.

**Components:****Butan-2-one O,O',O''-(methylsilyldiyl)trioxime:**

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 422  
Result: negative

Effects on foetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 422  
Result: negative

**Ethyl methyl ketoxime:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat  
Application Route: Ingestion  
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 414  
Result: negative

**NEUTRAL SILICONE WEATHER SEALANT  
CLEAR**

Version	Revision Date:	SDS Number:	Date of last issue: 19.06.2024
7.0	21.11.2024	10591859-00011	Date of first issue: 17.03.2011

---

**Butan-2-one O,O',O''-(vinylsilyldiyl)trioxime:**

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 422  
Result: negative  
Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 422  
Result: negative  
Remarks: Based on data from similar materials

**3-(2-Aminoethylamino) propyltrimethoxysilane:**

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: Ingestion  
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 414  
Result: negative

**STOT - single exposure**

May cause damage to organs (Upper respiratory tract) if inhaled.

**Components:****Butan-2-one O,O',O''-(methylsilyldiyl)trioxime:**

Assessment : May cause drowsiness or dizziness.  
Remarks : Based on data from similar materials

**Ethyl methyl ketoxime:**

Assessment : May cause drowsiness or dizziness.

Exposure routes : inhalation (dust/mist/fume)  
Target Organs : Upper respiratory tract  
Assessment : Shown to produce significant health effects in animals at concentrations of 1.0 mg/l/4h or less.

**NEUTRAL SILICONE WEATHER SEALANT  
CLEAR**

Version	Revision Date:	SDS Number:	Date of last issue: 19.06.2024
7.0	21.11.2024	10591859-00011	Date of first issue: 17.03.2011

---

**Butan-2-one O,O',O''-(vinylsilyldiyl)trioxime:**

Assessment : May cause drowsiness or dizziness.  
Remarks : Based on data from similar materials

**3-(2-Aminoethylamino) propyltrimethoxysilane:**

Exposure routes : Ingestion  
Target Organs : Central nervous system, optic nerve  
Assessment : May cause damage to organs.  
Remarks : Based on data from similar materials

**STOT - repeated exposure**

Not classified based on available information.

**Components:****Butan-2-one O,O',O''-(methylsilyldiyl)trioxime:**

Exposure routes : Ingestion  
Target Organs : Blood  
Assessment : Shown to produce significant health effects in animals at concentrations of 10 mg/kg bw or less.  
Remarks : Based on data from similar materials

**Ethyl methyl ketoxime:**

Exposure routes : Ingestion  
Target Organs : Blood  
Assessment : Shown to produce significant health effects in animals at concentrations of >10 to 100 mg/kg bw.

**Butan-2-one O,O',O''-(vinylsilyldiyl)trioxime:**

Exposure routes : Ingestion  
Target Organs : Blood  
Assessment : Shown to produce significant health effects in animals at concentrations of >10 to 100 mg/kg bw.  
Remarks : Based on data from similar materials

**3-(2-Aminoethylamino) propyltrimethoxysilane:**

Exposure routes : inhalation (dust/mist/fume)  
Target Organs : Respiratory Tract  
Assessment : Shown to produce significant health effects in animals at concentrations of >0.02 to 0.2 mg/l/6h/d.

**Repeated dose toxicity****Components:****Butan-2-one O,O',O''-(methylsilyldiyl)trioxime:**

Species : Rat



## NEUTRAL SILICONE WEATHER SEALANT CLEAR

Version	Revision Date:	SDS Number:	Date of last issue: 19.06.2024
7.0	21.11.2024	10591859-00011	Date of first issue: 17.03.2011

---

LOAEL : > 1.7 mg/l  
 Application Route : inhalation (vapour)  
 Exposure time : 26 Months  
 Remarks : Based on data from similar materials

Species : Rat, male  
 NOAEL : > 10 - 100 mg/kg  
 Application Route : Ingestion  
 Exposure time : 13 Weeks  
 Remarks : Based on data from similar materials

### Ethyl methyl ketoxime:

Species : Rat  
 LOAEL : 0.054 mg/l  
 Application Route : inhalation (vapour)  
 Exposure time : 26 Months

Species : Rat, male  
 NOAEL : 25 mg/kg  
 Application Route : Ingestion  
 Exposure time : 13 Weeks

### Butan-2-one O,O',O''-(vinylsilylidyne)trioxime:

Species : Rat  
 LOAEL : > 1.7 mg/l  
 Application Route : inhalation (vapour)  
 Exposure time : 26 Months  
 Remarks : Based on data from similar materials

Species : Rat, male  
 NOAEL : > 10 - 100 mg/kg  
 Application Route : Ingestion  
 Exposure time : 13 Weeks  
 Remarks : Based on data from similar materials

### 3-(2-Aminoethylamino) propyltrimethoxysilane:

Species : Rat  
 NOAEL : >= 500 mg/kg  
 Application Route : Ingestion  
 Exposure time : 44 Days

Species : Rat  
 NOAEL : 0.015 mg/l  
 LOAEL : 0.045 mg/l  
 Application Route : inhalation (dust/mist/fume)  
 Exposure time : 13 Weeks  
 Method : OECD Test Guideline 413

## NEUTRAL SILICONE WEATHER SEALANT CLEAR

Version	Revision Date:	SDS Number:	Date of last issue: 19.06.2024
7.0	21.11.2024	10591859-00011	Date of first issue: 17.03.2011

---

### Aspiration toxicity

Not classified based on available information.

### Components:

#### **Distillates (petroleum), hydrotreated middle:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

---

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

#### Components:

#### **Distillates (petroleum), hydrotreated middle:**

Toxicity to fish	:	LC50 (Oncorhynchus mykiss (rainbow trout)): > 87,556 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 1,000 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	:	EC50 (Selenastrum capricornutum (green algae)): > 1,000 mg/l Exposure time: 72 h
Toxicity to fish (Chronic toxicity)	:	NOELR: > 1,000 mg/l Exposure time: 28 d
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOELR: 5 mg/l Exposure time: 21 d
Toxicity to microorganisms	:	EC50: > 100 mg/l Exposure time: 3 h

#### **Butan-2-one O,O',O''-(methylsilyldiylidene)trioxime:**

Toxicity to fish	:	EC50 (Oncorhynchus mykiss (rainbow trout)): > 120 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 120 mg/l Exposure time: 48 h Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	:	ErC50 (Pseudokirchneriella subcapitata (green algae)): 94 mg/l Exposure time: 72 h Method: OECD Test Guideline 201

**NEUTRAL SILICONE WEATHER SEALANT  
CLEAR**

Version	Revision Date:	SDS Number:	Date of last issue: 19.06.2024
7.0	21.11.2024	10591859-00011	Date of first issue: 17.03.2011

---

NOEC (*Pseudokirchneriella subcapitata* (green algae)): 30 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (*Daphnia magna* (Water flea)): > 1 mg/l  
Exposure time: 21 d  
Method: OECD Test Guideline 211  
Remarks: Based on data from similar materials

Toxicity to microorganisms : EC50: > 1,000 mg/l  
Exposure time: 3 h  
Method: OECD Test Guideline 209

**Ethyl methyl ketoxime:**

Toxicity to fish : LC50 (*Oryzias latipes* (Japanese medaka)): > 100 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (*Daphnia magna* (Water flea)): 201 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : ErC50 (*Scenedesmus capricornutum* (fresh water algae)): 11.8 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

NOEC (*Scenedesmus capricornutum* (fresh water algae)): 2.56 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (*Daphnia magna* (Water flea)): > 100 mg/l  
Exposure time: 21 d  
Method: OECD Test Guideline 211

Toxicity to microorganisms : EC50 (*Pseudomonas putida*): 281 mg/l  
Exposure time: 17 h

**Butan-2-one O,O',O''-(vinylsilylidyne)trioxime:**

Toxicity to fish : LC50 (*Oryzias latipes* (Japanese medaka)): > 100 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203  
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (*Daphnia magna* (Water flea)): > 100 mg/l  
Exposure time: 48 h

## NEUTRAL SILICONE WEATHER SEALANT CLEAR

Version	Revision Date:	SDS Number:	Date of last issue: 19.06.2024
7.0	21.11.2024	10591859-00011	Date of first issue: 17.03.2011

---

Method: OECD Test Guideline 202  
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : ErC50 (*Scenedesmus capricornutum* (fresh water algae)): > 10 - 100 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

NOEC (*Scenedesmus capricornutum* (fresh water algae)): > 1 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (*Daphnia magna* (Water flea)): > 1 mg/l  
Exposure time: 21 d  
Method: OECD Test Guideline 211  
Remarks: Based on data from similar materials

Toxicity to microorganisms : EC50 (*Pseudomonas putida*): > 100 mg/l  
Exposure time: 17 h  
Remarks: Based on data from similar materials

### **3-(2-Aminoethylamino) propyltrimethoxysilane:**

Toxicity to fish : LC50 (*Danio rerio* (zebra fish)): > 100 mg/l  
Exposure time: 96 h  
Method: Directive 67/548/EEC, Annex V, C.1.  
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EL50 (*Daphnia magna* (Water flea)): > 10 - 100 mg/l  
Exposure time: 48 h  
Test substance: Water Accommodated Fraction  
Method: Directive 67/548/EEC, Annex V, C.2.  
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : ErC50 (*Pseudokirchneriella subcapitata* (green algae)): > 1 - 10 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

NOEC (*Pseudokirchneriella subcapitata* (green algae)): > 1 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (*Daphnia magna* (Water flea)): > 1 mg/l  
Exposure time: 21 d

**NEUTRAL SILICONE WEATHER SEALANT  
CLEAR**

Version 7.0      Revision Date: 21.11.2024      SDS Number: 10591859-00011      Date of last issue: 19.06.2024  
Date of first issue: 17.03.2011

---

ic toxicity)      Remarks: Based on data from similar materials

Toxicity to microorganisms      :      EC10 (Pseudomonas putida): > 1 mg/l  
Exposure time: 16 h  
Method: DIN 38 412 Part 8  
Remarks: Based on data from similar materials

**Persistence and degradability****Components:****Distillates (petroleum), hydrotreated middle:**

Biodegradability      :      Result: Inherently biodegradable.

**Butan-2-one O,O',O''-(methylsilyldiyl)trioxime:**

Biodegradability      :      Result: Not readily biodegradable.  
Biodegradation: 28 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301C

**Ethyl methyl ketoxime:**

Biodegradability      :      Result: Not readily biodegradable.  
Biodegradation: 27 %  
Exposure time: 21 d

**Butan-2-one O,O',O''-(vinylsilyldiyl)trioxime:**

Biodegradability      :      Result: not rapidly degradable  
Biodegradation: 0 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301A  
Remarks: Based on data from similar materials

**3-(2-Aminoethylamino) propyltrimethoxysilane:**

Biodegradability      :      Result: Not readily biodegradable.  
Method: Regulation (EC) No. 440/2008, Annex, C.4-A  
Remarks: Based on data from similar materials

**Bioaccumulative potential****Components:****Butan-2-one O,O',O''-(methylsilyldiyl)trioxime:**

Partition coefficient: n-      :      log Pow: 0.59 - 0.65  
octanol/water

**Ethyl methyl ketoxime:**

**NEUTRAL SILICONE WEATHER SEALANT  
CLEAR**

Version	Revision Date:	SDS Number:	Date of last issue: 19.06.2024
7.0	21.11.2024	10591859-00011	Date of first issue: 17.03.2011

---

Bioaccumulation : Species: Cyprinus carpio (Carp)  
Bioconcentration factor (BCF): 0.5 - 0.6  
Method: OECD Test Guideline 305

Partition coefficient: n-  
octanol/water : log Pow: 0.63

**Butan-2-one O,O',O''-(vinylsilyldiyl)trioxime:**

Bioaccumulation : Species: Cyprinus carpio (Carp)  
Bioconcentration factor (BCF): 0.5 - 2.5  
Remarks: Based on data from similar materials

Partition coefficient: n-  
octanol/water : log Pow: 0.59 - 0.65

**3-(2-Aminoethylamino) propyltrimethoxysilane:**

Partition coefficient: n-  
octanol/water : log Pow: -3.3  
Remarks: Calculation

**Mobility in soil**

No data available

**Other adverse effects**

No data available

---

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

Waste from residues : Do not dispose of waste into sewer.  
Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
If not otherwise specified: Dispose of as unused product.

---

**SECTION 14. TRANSPORT INFORMATION****International Regulations****UNRTDG**

UN number : Not applicable  
Proper shipping name : Not applicable  
Class : Not applicable  
Subsidiary risk : Not applicable  
Packing group : Not applicable  
Labels : Not applicable

## NEUTRAL SILICONE WEATHER SEALANT CLEAR

Version	Revision Date:	SDS Number:	Date of last issue: 19.06.2024
7.0	21.11.2024	10591859-00011	Date of first issue: 17.03.2011

---

Environmentally hazardous : no

### IATA-DGR

UN/ID No. : Not applicable  
 Proper shipping name : Not applicable  
 Class : Not applicable  
 Subsidiary risk : Not applicable  
 Packing group : Not applicable  
 Labels : Not applicable  
 Packing instruction (cargo aircraft) : Not applicable  
 Packing instruction (passenger aircraft) : Not applicable

### IMDG-Code

UN number : Not applicable  
 Proper shipping name : Not applicable  
 Class : Not applicable  
 Subsidiary risk : Not applicable  
 Packing group : Not applicable  
 Labels : Not applicable  
 EmS Code : Not applicable  
 Marine pollutant : Not applicable

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### National Regulations

#### ADG

UN number : Not applicable  
 Proper shipping name : Not applicable  
 Class : Not applicable  
 Subsidiary risk : Not applicable  
 Packing group : Not applicable  
 Labels : Not applicable  
 Hazchem Code : Not applicable

### Special precautions for user

Not applicable

---

## SECTION 15. REGULATORY INFORMATION

### Safety, health and environmental regulations/legislation specific for the substance or mixture

Therapeutic Goods (Poisons Standard) Instrument : No poison schedule number allocated (Please use the original publication to check for specific uses, specific conditions or threshold limits that might apply for this chemical)

Prohibition/Licensing Requirements : There is no applicable prohibition, authorisation and restricted use requirements, including for carcinogens referred to in Schedule 10 of

**NEUTRAL SILICONE WEATHER SEALANT  
CLEAR**

Version	Revision Date:	SDS Number:	Date of last issue: 19.06.2024
7.0	21.11.2024	10591859-00011	Date of first issue: 17.03.2011

---

the model WHS Act and Regulations.

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)  
Volatile organic compounds (VOC) content: 5 g/l

**The components of this product are reported in the following inventories:**

AIIC : All ingredients listed or exempt.

---

**SECTION 16: ANY OTHER RELEVANT INFORMATION****Further information**

Revision Date : 21.11.2024

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

Date format : dd.mm.yyyy

**Full text of other abbreviations**

AU OEL : Australia. Workplace Exposure Standards for Airborne Contaminants.

AU OEL / TWA : Exposure standard - time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECl - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect



**NEUTRAL SILICONE WEATHER SEALANT  
CLEAR**

Version	Revision Date:	SDS Number:	Date of last issue: 19.06.2024
7.0	21.11.2024	10591859-00011	Date of first issue: 17.03.2011

---

Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECl - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

AU / EN